

# HOT JET S: Small and powerful.

As the most compact hot-air hand tool from Leister, the HOT JET S' low weight of 600 grams (including cord and slim handle) ensures high-powered, fatigue-free welding.



Especially suited to facilitate tasks in difficult to access areas.

Hot-air hand tool

## HOT JET S



- The smallest Leister hot-air hand tool
- Stepless, electronically controlled temperature
- Stepless, electronically controlled air flow
- Low noise
- Flexible, integrated tool stand

### Technical data

Voltage	V~	120 / 230
Power	W	460 / 460
Temperature	°C	20 – 600
Size (L × Ø)	mm	235 × 70, handle Ø 40
Weight	kg	0.4 (without 2 m cord)
Conformity mark	CE	
Approval mark		
Protection class II		

### Article No.:

100.648	HOT JET S, 230 V / 460 W, with Euro plug
100.862	HOT JET S, 120 V / 460 W, without plug
100.854	HOT JET S, 230 V / 460 W, with AUS plug

## Accessories HOT JET S











	<b>107.141</b>	15 mm wide slot nozzle, push-fit
	<b>107.142</b>	20 mm wide slot nozzle, push-fit
	<b>107.144</b>	Ø 5 mm tubular nozzle, push-fit
	<b>105.567</b>	Ø 5 × 150 mm extension nozzle, straight
	<b>105.556</b>	20 mm angled nozzle, 90° angled, push-fit
	<b>106.996</b>	Tacking nozzle, push-fit on Ø 5 mm tubular nozzle
	<b>106.989</b>	3 mm speed welding nozzle, push-fit on Ø 5 mm tubular nozzle
	<b>106.990</b>	4 mm speed welding nozzle, push-fit on Ø 5 mm tubular nozzle
	<b>106.991</b>	5 mm speed welding nozzle, push-fit on Ø 5 mm tubular nozzle
	<b>106.992</b>	5.7 mm, A profilee speed welding nozzle, push-fit
	<b>106.993</b>	7 mm, B profilee speed welding nozzle, push-fit
	<b>105.431</b>	3 mm speed welding nozzle, with small air-slide, push-fit on Ø 5 mm tubular nozzle
	<b>105.432</b>	4 mm speed welding nozzle, with small air-slide, push-fit on Ø 5 mm tubular nozzle
	<b>105.433</b>	5 mm speed welding nozzle, with small air-slide, push-fit on Ø 5 mm tubular nozzle



HOT JET S with angled nozzle welding a T-joint on the roof.



Fitting a solder shrink connection with the HOT JET S outfitted with a push-fit sieve reflector.

	<b>107.137</b> 8 mm speed welding nozzle for tape welding, push-fit on $\varnothing$ 5 mm tubular nozzle
	<b>107.139</b> 4.5 x 12 mm speed welding nozzle for fillet weld, push-fit on $\varnothing$ 5 mm tubular nozzle
	<b>107.324</b> 12 x 10 mm sieve reflector, push-fit on $\varnothing$ 5 mm tubular nozzle
	<b>107.146</b> $\varnothing$ 2 mm soldering nozzle
	<b>107.151</b> $\varnothing$ 4 mm soldering nozzle
	<b>107.148</b> $\varnothing$ 3 x 1.5 mm soldering nozzle, oval
	<b>107.310</b> 35 x 20 mm sieve reflector, push-fit
	<b>107.311</b> 50 x 35 mm sieve reflector, push-fit
	<b>107.312</b> 25 x 30 mm spoon reflector, push-fit
	<b>107.305</b> 15 x 25 mm ironing nozzle
	<b>143.831</b> Nozzle adapter for screw-on nozzles
	<b>114.734</b> Ski repair nozzle without base plate
	<b>100.818</b> 230 V / 435 W heating element
	<b>103.607</b> 120 V / 435 W heating element

Small and handy: The HOT JET S is perfect when welding complicated details in billboard and tarpaulin applications.

